


Data sheet Polytronik[®] Toroidal transformer

Part no.:	RSO 826019
Description:	RKT 50VA/ 230V/ 2x9,0V 2x2,78A
Safety isolating transformer according to:	EN 61558-2-6 / VDE 0570
Power [VA]:	50
Input voltage [AC]:	230 V +-10%
Output voltage [AC]:	2 x 9,00 V
Output current [AC]:	2 x 2,78 A
Frequency [Hz]:	50/60
Dielectric strength PRI - SEC [AC]:	4400 V
Efficiency [%]:	83
Power loss at no-load [W]:	0,48
Maximum ambient temperature t_a [°C]:	40
Temperature class:	B (130°C)



construction only

Schematic:



possible interconnection: parallel connection **9.0V / 5.56A** = connect black with violet and red with white
 series connection **18.0V / 2.78A** = connect red with violet

Approval marks: CE; ENEC; UL508 (E182061)

Connections: primary wires 210 mm long
 secondary wires 200 mm long

Model: toroidal transformer without mounting accessories

Appliance class: prepared for class II

Protection class: IP 00

Recommended fuse ratings:	primary	0.315 AT	(IEC60127-2-5)
	secondary 1	3.15 AT	(IEC60127-2-3)
	secondary 2	3.15 AT	(IEC60127-2-3)

Dimensions: diameter approx. = 76 mm
 height approx. = 34 mm

Weight: approx. 0.58 kg