


Data sheet Polytronik[®] Toroidal transformer

Part no.:	RSO 826025
Description:	RKT 100VA/ 230V/ 2x9,0V 2x5,56A
Safety isolating transformer according to:	EN 61558-2-6 / VDE 0570
Power [VA]:	100
Input voltage [AC]:	230 V +-10%
Output voltage [AC]:	2 x 9,00 V
Output current [AC]:	2 x 5,56 A
Frequency [Hz]:	50/60
Dielectric strength PRI - SEC [AC]:	4400 V
Efficiency [%]:	86
Power loss at no-load [W]:	0,99
Maximum ambient temperature t_a [°C]:	40
Temperature class:	B (130°C)



Schematic:



possible interconnection: parallel connection **9.0V / 11.12A** = connect black with violet and red with white
 series connection **18.0V / 5.56A** = connect red with violet

Approval marks: CE; ENEC; UL508 (E182061)

Connections: primary wires 200 mm long
 secondary wires 200 mm long

Model: toroidal transformer without mounting accessories

Appliance class: prepared for class II

Protection class: IP 00

Recommended fuse ratings:	primary	0.630 AT	(IEC60127-2-5)
	secondary 1	6.30 AT	(IEC60127-2-3)
	secondary 2	6.30 AT	(IEC60127-2-3)

Dimensions:	diameter approx. =	89 mm
	height approx. =	42 mm

Weight: approx. 1.04 kg