



## Data sheet Polytronik® Toroidal transformer

Part no.:	<b>RSO 826037</b>
Description:	RKT 200VA/ 230V/ 2x9,0V 2x11,12A
Safety isolating transformer according to:	EN 61558-2-6 / VDE 0570
Power [VA]:	200
Input voltage [AC]:	230 V +-10%
Output voltage [AC]:	2 x 9,00 V
Output current [AC]:	2 x 11,12 A
Frequency [Hz]:	50/60
Dielectric strength PRI - SEC [AC]:	4400 V
Efficiency [%]:	90
Power loss at no-load [W]:	1,86
Maximum ambient temperature $t_a$ [°C]:	40
Temperature class:	B (130°C)



### Schematic:



possible interconnection: parallel connection **9.0V / 22.24A** = connect black with violet and red with white  
 series connection **18.0V / 11.12A** = connect red with violet

Approval marks: CE; ENEC; UL508 (E182061)

Connections: primary wires 200 mm long  
 secondary wires 200 mm long

Model: toroidal transformer without mounting accessories

Appliance class: prepared for class II

Protection class: IP 00

Recommended fuse ratings:	primary	1.00 AT	(IEC60127-2-5)
	secondary 1	12.5 AT	(IEC60127-2-3)
	secondary 2	12.5 AT	(IEC60127-2-3)

Dimensions:	diameter approx. =	113 mm
	height approx. =	48 mm

Weight: approx. 2.00 kg