


Data sheet Polytronik® Toroidal transformer

Part no.:	RTO 826042
Description:	RKT 200VA/ 230V/ 2x30,0V 2x3,33A
Safety isolating transformer according to:	EN 61558-2-4 / VDE 0570
Power [VA]:	200
Input voltage [AC]:	230 V +-10%
Output voltage [AC]:	2 x 30,00 V
Output current [AC]:	2 x 3,33 A
Frequency [Hz]:	50/60
Dielectric strength PRI - SEC [AC]:	4400 V
Efficiency [%]:	90
Power loss at no-load [W]:	1,86
Maximum ambient temperature t_a [°C]:	40
Temperature class:	B (130°C)



Schematic:



possible interconnection: parallel connection **30.0V / 6.66A** = connect black with violet and red with white
 series connection **60.0V / 3.33A** = connect red with violet

Approval marks: CE; ENEC; UL508 (E182061)

Connections: primary wires 200 mm long
 secondary wires 210 mm long

Model: toroidal transformer without mounting accessories

Appliance class: prepared for class II

Protection class: IP 00

Recommended fuse ratings:	primary	1.00 AT	(IEC60127-2-5)
	secondary 1	3.50 AT	(IEC60127-2-3)
	secondary 2	3.50 AT	(IEC60127-2-3)

Dimensions: diameter approx. = 113 mm
 height approx. = 48 mm

Weight: approx. 2.00 kg